

FIELD SET-UP PROCEDURE FOR LISTER STREET FIELDS 1A & 1B.

The following is the set-up procedure for both the pitches at Lister Street precinct.

This is a written guide only and ALL teams doing the field set up should have representatives attend a practical demonstration of the goal set up procedure.

These practical demonstrations will be done on every Saturday morning, beginning at 07:00AM, up until Round 10 on the 22nd June 2024.

1. Open the small key box on the side of the Uniform shop using the 'Sunnybank' key.
2. Using the key from inside, open the padlock on the floor lock on the second roller door.

Once inside

3. Collect four short corner flags – usually tied together and at the LHS of roller door.
4. Collect two of the triangular goal ends- usually tied together and located at the LHS of the roller door and a black goal bag – usually located on the RHS of the roller door.

5. Collect 4no. collapsible benches – usually located next to the black goal bags,

Once all these elements have been collected proceed to the relevant pitch.

6. Place corner flags at each corner.

7. Unfold and place 2no. collapsible benches on either side of the permanent goals. Ensure legs are folded down completely and benches locked with red lock on middle set of legs.

8. Take out base bar & crossbar from goal bag. Put both together. Crossbar has arrows embossed on it, is harder to piece together and has a slight curve when fully constructed. Base bar has stake points marked at either end.

9. Triangular end pieces should be placed at both ends of the cross bar & base bar. There is a RH and LH end piece and this is determined by the “Quickplay” logo facing into the field of play.

10. Attach the basebar & crossbar to the triangular end pieces.

The basebar is not end specific however, the crossbar must be attached so the embossed arrows point upwards and the bar curves slightly upwards.

This is critical to the correct construction of the completed goal.

11. Once the frame is constructed, unroll the net. There are two small white tabs at either end on one of the lead lines at the intersection of the top lead line and the side lead line.

Stretch this intersecting area over each of the top corners of the goal frame and tie in place with a supplied rubber toggle.

12. Tie a minimum of 6 no. rubber toggles to the top lead line, wrap the top of the net around the crossbar and secure by wrapping rubber toggle around crossbar and tie back into itself.

13. Locate bottom lead line and intersecting side line and stretch this intersecting area over the bottom corner of the goal frame – similar to top – and tie in place.

14. Tie a minimum of 5no. rubber toggles to the bottom lead line, wrap around the base bar – similarly to the crossbar and tie the rubber toggle back into itself.

15. Locate the lead line for the front of the triangular side piece of the net and the lead line for the base lead line of this triangular section stretch this intersection area down and hook it over the base of the front uprights at either end and secure net to upright using a minimum of 4no. rubber toggles.

16. Locate the internal intersecting side lead line at either end and tie – using a minimum of three rubber toggles (1no. above bend and 2no. below bend) secure this lead line to the black aluminium arms at either end of the goal frame.

17. Tie the bottom lead line of the net triangular section to the base of the constructed end triangular section with a minimum of 2no. additional rubber toggles.

The net and goal frame should now resemble a normal goal and be relatively sturdy with the goal

net being fairly taut at both the back and at both sides.

It should be constructed so as the ball cannot enter the goal through any part of the side panels.

18. The fully constructed goals should now be positioned in the centre of the 12m X 6m marked goalkeeper's box, with the front of the uprights lined up with the inside of the marked goal line at the rear of the goalkeeper's box and using the supplied U pegs, secured to the ground.

*If only 3 no U pegs available, place 1no. at either end of the goals at the front LH & RH side stake points and 1no. at centre of the basebar at rear of the goal.

*If 4no. available, place 1no U peg at each of the LH & RH front side stake points and 1 no. at the LH and RH stake points on the basebar.

Move to the other end of the small field & repeat steps 8 – 18 to complete the field setup.

18. Check field for any rubbish or potentially dangerous items & place in supplied wheelie bins around Lister St. precinct.

Field set up should be completed ready for the referee's inspection at least 10 mins. before the scheduled kick off time of the first game.